

Tred-MOR®

Carpet Tile Cushion

- ▶ Made of SYNTHETIC RUBBER
- ▶ PVI Technology

SPECIFICATIONS

	Modular PVI™	Test Standard
Product Codes:	BV0341	
Composition:	100% Synthetic Rubber	
Thickness:	0.156"	ASTM D3574
Density:	33 lbs/ft ³ or 62 oz/yd ²	ASTM D3574
R-Value:	0.270	
Color:	Green	
Moisture Barrier:	StainSTOP™	
Backing Top/Bottom:	Non-Woven/Non-Woven	
Roll Size:	15 yd ²	
Dimensions:	54" x 30'	

PERFORMANCE

CLD psi @ 25% & 65% Deflec. Min:	7.0 & 45.0	Method 601/12151
Compression Set, Max %	15	ASTM D3676
Breaking Strength Length/Width, Min. psi	45/41	ASTM D2646

ACOUSTICAL PROPERTIES

Impact Insulation Class (IIC):	65	ASTM 492
Sound Transmission Class (STC):	52	ASTM C423-81
Delta (ΔIIC):	32	

FLAMMABILITY

Pill Test:	Passes	DOC-FF 1-70
Smoke Density Test (NIST):	Passes	ASTM E662-97
Radiant Panel Test:	N/A – cushion must be tested in combination with carpet	ASTM E648

PROTECTION

Antimicrobial:	Guardian™	EPA-Registered
Hypoallergenic:	Yes	
Indoor Air Quality:	Certified	CRI Green Label Plus
Warranty:	Life of the Carpet Tile	

