

PAD-LOC

MARITIME CARPET SUPPORT® – 180

Product Features

- Dramatically reduces carpet wear and extends appearance retention
- Fuel saver – 65% less weight than comparable products
- Low-profile design provides excellent door clearance
- Noise reduction – rebond cushion is excellent for reducing airborne and impact-noise transmission
- Helps reduce body stress and fatigue
- Fresh Dimension® antimicrobial inhibits the growth of mold, mildew, and odor-causing bacteria
- Recyclable at the end of its useful life

Certifications

- Complies with SOLAS and U.S. Coast Guard requirements
- Wheel Mark-certified as defined by EU directive on marine equipment
- Passes International Maritime Organization fire codes
- Green Label Plus-certified for good indoor air quality
- ISO 9000 Compliant: LP9000 Certified

SPECIFICATIONS

	Standard	Metric
Composition	Rebond Foam	Rebond Foam
Density	11.5 lbs/ft ³	184 kg/m ³
Weight	26 oz/yd ²	881.5 g/m ²
Thickness	0.180" (+/- 0.020")	4.6 mm (+/- 0.508 mm)
Dimensions	6' x 60'	1.83 m x 18.3 m
Roll Size	360 ft ²	33.4 m ²
Compression Force Deflection @ 25% / 65% deflection	3.2 psi/18.6 psi	22 kPa/128.2 kPa
Compression Set (Max)	14.4%	14.4%
Tensile Strength	28 psi	193 kPa
Impact Sound Transmission (ASTM E492-77)	IIC 71	IIC 71
Commercial Traffic Class	Heavy	Heavy
IMO FTPC Part 5, IMO Res. A.653 (16)	Passes	Passes
IMO FTPC Part 2, ISO 5659-2:2006	Passes	Passes
Wheel Mark Certificate	LRD No. 0525	LRD No. 0525
Lloyd's Register Certificate of Fire Approval	SAS F090321	SAS F090321
Antimicrobial Treated	Fresh Dimension®	Fresh Dimension®
CRI Indoor Air Quality Testing	Green Label Plus	Green Label Plus
Assigned U.S. Coast Guard Module B No.	164.117/EC0038	164.117/EC0038

COMMERCIAL WARRANTY

Please visit LPFlooringProducts.com/pad-loc for detailed warranty information.



Leggett & Platt
FLOORING PRODUCTS